

| | |
|---|---------------------------------------|
| <p>PNP型 小功率 贴片开关三极管 PNP Switching Transistor SMD</p> | <p>MMBT3906 对应其他工业型号 3906</p> |
| <ul style="list-style-type: none"> ■ Excellent hFE linearity ■ Low noise ■ Transistor Polarity: PNP ■ Transistor pinout: BEC ■ SOT-23 Package ■ Marking Code: 2A ■ hFE: 100~200, 200~300 | |

| | | |
|--|---|---|
| <p style="text-align: center;">Inner circuit</p>  <p style="text-align: center;">SOT-23 内部结构</p> | <p style="text-align: center;">MMBT3906</p>  <p style="text-align: center;">SOT-23 管脚排列</p> | <p style="text-align: center;">元件标识 (打印)</p>  <p style="text-align: center;">DEVICE MARKING</p> |
|--|---|---|

■ CLASSIFICATION OF hFE

| | | |
|-------|---------|---------|
| RANK | L | H |
| RANGE | 100~200 | 200~300 |

■ MAXIMUM RATINGS

| Symbol | Parameter | Value | Unit |
|-----------------|--|----------|------|
| V_{CB0} | Collector-Base Voltage | -40 | V |
| V_{CEO} | Collector-Emitter Voltage | -40 | V |
| V_{EBO} | Emitter-Base Voltage | -6 | V |
| I_c | Collector Current | -200 | mA |
| P_c | Collector Power Dissipation | 300 | mW |
| $R_{\theta JA}$ | Thermal Resistance From Junction To Ambient | 417 | °C/W |
| T_J, T_{stg} | Operation Junction and Storage Temperature Range | -55~+150 | °C |

■ ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$ unless otherwise noted 25°C)

| Characteristic | Test Condition | Symbol | Min | Typ | Max | Unit |
|--------------------------------------|--|-----------------|------|-----|------|------------------|
| Collector-Emitter Breakdown Voltage | $I_B=0, I_C=-1\text{mA}$ | $V_{(BR)CEO}$ | -40 | -- | -- | V |
| Collector-Base Breakdown Voltage | $I_E=0, I_C=-10\mu\text{A}$ | $V_{(BR)CBO}$ | -40 | -- | -- | |
| Emitter-Base Breakdown Voltage | $I_C=0, I_E=-10\mu\text{A}$ | $V_{(BR)EBO}$ | -6.0 | -- | -- | |
| Base Cutoff Current | $V_{CE}=-30\text{V}, V_{EB}=-3\text{V}$ | I_{BEX} | -- | -- | -50 | nA |
| Collector Cutoff Current | $V_{CE}=-30\text{V}, V_{EB}=-3\text{V}$ | I_{CEX} | -- | -- | -50 | |
| DC Current Gain | $I_C=-0.1\text{mA}, V_{CE}=-1\text{V}$ | hFE | 40 | -- | -- | |
| | $I_C=-1\text{mA}, V_{CE}=-1\text{V}$ | | 70 | -- | -- | |
| | $I_C=-10\text{mA}, V_{CE}=-1\text{V}$ | | 100 | -- | 300 | |
| | $I_C=-50\text{mA}, V_{CE}=-1\text{V}$ | | 60 | -- | -- | |
| | $I_C=-100\text{mA}, V_{CE}=-1\text{V}$ | | 30 | -- | 300 | |
| Collector-Emitter Saturation Voltage | $I_C=-10\text{mA}, I_B=-1\text{mA}$ | $V_{CE(sat)}$ | -- | -- | 0.25 | V |
| | $I_C=-50\text{mA}, I_B=-5\text{mA}$ | | -- | -- | 0.40 | |
| Base-Emitter Saturation Voltage | $I_C=-10\text{mA}, I_B=-1\text{mA}$ | $V_{BE(sat)}$ | 0.65 | -- | 0.85 | |
| | $I_C=-50\text{mA}, I_B=-5\text{mA}$ | | -- | -- | 0.95 | |
| Current-Gain-Bandwidth Product | $I_C=-10\text{mA}, V_{CE}=-20\text{V}, f=100\text{MHz}$ | f_T | 300 | -- | -- | MHz |
| Collector Output Capacitance | $V_{CB}=-5\text{V}, I_E=0, f=1\text{MHz}$ | C_{OB} | -- | -- | 4.0 | pF |
| Input Capacitance | $V_{EB}=-0.5\text{V}, I_C=0, f=1\text{MHz}$ | C_{ibo} | -- | -- | 8.0 | |
| Input Impedance | $I_C=-1\text{mA}, V_{CE}=-10\text{V}, f=1\text{kHz}$ | h _{ie} | 1.0 | -- | 10 | K Ω |
| Voltage Feedback Ratio | $I_C=-1\text{mA}, V_{CE}=-10\text{V}, f=1\text{kHz}$ | h _{re} | 0.5 | -- | 8.0 | $\times 10^{-4}$ |
| Small-Signal Current Gain | $I_C=-1\text{mA}, V_{CE}=-10\text{V}, f=1\text{kHz}$ | hFE | 100 | -- | 400 | |
| Output Admittance | $I_C=-1\text{mA}, V_{CE}=-10\text{V}, f=1\text{kHz}$ | h _{oe} | 1.0 | -- | 40 | $\mu\Omega$ |
| Noise Figure | $I_C=-100\mu\text{A}, V_{CE}=-5\text{V}, R_s=1\text{K}\Omega, f=1\text{kHz}$ | NF | -- | -- | 5.0 | db |
| Delay Time | $V_{CC}=-30\text{V}, V_{BE(off)}=-0.5\text{V}$ $I_C=-10\text{mA}, I_{B1}=-1\text{mA}$ | t_d | -- | -- | 35 | nS |
| Rise Time | | t_r | -- | -- | 35 | |
| Storage Time | $V_{CC}=-30\text{V}, I_C=-10\text{mA}$ $I_{B1} = I_{B2} = -1\text{mA}$ | t_s | -- | -- | 225 | |
| Fall Time | | t_f | -- | -- | 75 | |







1. FR-5 = $1.0 \times 0.75 \times 0.062$ in.

2. Alumina = $0.4 \times 0.3 \times 0.024$ in. 99.5% alumina.


3. Pulse Width $\leq 300\mu\text{s}$; Duty Cycle $\leq 2.0\%$.

4. Pulse Test: Pulse Width $\leq 300\mu\text{s}$; Duty Cycle $\leq 2.0\%$.

TYPICAL CHARACTERISTICS



■ DIMENSION




单位 (UNIT) : mm

| 序号 | 数值及公差 |
|--|-----------|
| A | 2.90±0.10 |
| B | 1.30±0.10 |
| C | 1.00±0.10 |
| D | 0.40±0.10 |
| E | 2.40±0.20 |
| G | 1.90±0.10 |
| H | 0.95±0.05 |
| J | 0.13±0.05 |
| K | 0.00-0.10 |
| M | ≥0.20 |
| N | 0.60±0.10 |
| P | 7±2° |
| Packing SOT-23 包装规格 SMD片式表面贴封装 包装方式: 载带卷盘包装 Tape & Reel, 3Kpcs/Reel 每卷数量3000只 (3Kpcs/Reel) 每盒数量45000只 (45Kpcs/BOX) 每箱数量180000只 (180Kpcs/Cartons) | |


SOT-23 Tape and reel

SOT-23 Embossed Carrier Tape




| Dimensions are in millimeter | | | | | | | | | | |
|------------------------------|------|------|------|-------|------|------|------|------|------|------|
| Pkg type | A | B | C | d | E | F | P0 | P | P1 | W |
| SOT-23 | 3.15 | 2.77 | 1.22 | Ø1.50 | 1.75 | 3.50 | 4.00 | 4.00 | 2.00 | 8.00 |

SOT-23 Tape Leader and Trailer



SOT-23 Reel



| Dimensions are in millimeter | | | | | | | | |
|------------------------------|---------|-------|-------|--------|--------|-------|------|-------|
| Reel Option | D | D1 | D2 | G | H | I | W1 | W2 |
| 7" Dia | Ø178.00 | 54.40 | 13.00 | R78.00 | R25.60 | R6.50 | 9.50 | 12.30 |

| REEL | Reel Size | Box | Box Size(mm) | Carton | Carton Size(mm) | G.W.(kg) |
|----------|-----------|------------|--------------|-------------|-----------------|----------|
| 3000 pcs | 7 inch | 45,000 pcs | 192×192×193 | 180,000 pcs | 404×404×214 | |