



Features

- 20V/8A,
 - $R_{DS(ON)} = 14m\Omega(\text{typ.}) @ V_{GS} = 4.5V$
 - $R_{DS(ON)} = 16m\Omega(\text{typ.}) @ V_{GS} = 2.5V$
- 100% UIS + R_g Tested
- Reliable and Rugged
- Lead Free and Green Devices Available (RoHS Compliant)
- ESD protection

Applications

- Li-Ion Battery Pack.
- DC-DC Buck Converters.

Pin Description



N-Channel MOSFET

Absolute Maximum Ratings ($T_A = 25^\circ\text{C}$ Unless Otherwise Noted)

Symbol	Parameter	Rating	Unit
Common Ratings			
V_{DSS}	Drain-Source Voltage	20	V
V_{GSS}	Gate-Source Voltage	± 10	
T_J	Maximum Junction Temperature	150	$^\circ\text{C}$
T_{STG}	Storage Temperature Range	-55 to 150	
I_S	Diode Continuous Forward Current	$T_A=25^\circ\text{C}$ 8	A
I_D	Continuous Drain Current	$T_A=25^\circ\text{C}$ 8	A
		$T_A=70^\circ\text{C}$ 6	
I_{DM}^a	Pulsed Drain Current	$T_A=25^\circ\text{C}$ 24	A
P_D^b	Maximum Power Dissipation	$T_A=25^\circ\text{C}$ 1.32	W
		$T_A=70^\circ\text{C}$ 0.8	
$R_{\theta JA}^b$	Thermal Resistance-Junction to Ambient	$t \leq 10\text{s}$ 54	$^\circ\text{C/W}$
		Steady State 95	$^\circ\text{C/W}$
I_{AS}^c	Avalanche Current, Single pulse	$L=0.1\text{mH}$ 16	A
E_{AS}^c	Avalanche Energy, Single pulse	$L=0.1\text{mH}$ 13	mJ

Note a : Pulse width limited by max. junction temperature.

Note b : $R_{\theta JA}$ steady state $t=999\text{s}$.

Note c : UIS tested and pulse width limited by maximum junction temperature 150°C (initial temperature $T_J=25^\circ\text{C}$)

Electrical Characteristics ($T_A = 25^\circ\text{C}$ Unless Otherwise Noted)


Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
Static Characteristics						
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS}=0V, I_{DS}=250\mu A$	20	-	-	V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS}=16V, V_{GS}=0V$ $T_J=85^\circ\text{C}$	-	-	1	μA
			-	-	30	
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_{DS}=250\mu A$	0.5	0.75	1	V
I_{GSS}	Gate Leakage Current	$V_{GS}=\pm 10V, V_{DS}=0V$	-	-	± 10	μA
$R_{DS(ON)}^d$	Drain-Source On-state Resistance	$V_{GS}=4.5V, I_{DS}=9A$ $T_J=125^\circ\text{C}$	-	14	17	m Ω
			-	17.5	-	
			$V_{GS}=2.5V, I_{DS}=8A$	-	16	
Gfs	Forward Transconductance	$V_{DS}=5V, I_{DS}=8A$	-	24	-	S
Diode Characteristics						
V_{SD}^d	Diode Forward Voltage	$I_{SD}=1.5A, V_{GS}=0V$	-	0.72	1.1	V
t_{rr}	Reverse Recovery Time	$V_{DD}=15V,$ $F_{WD}=5A$ $I_{induct} I=0.1mH$	-	10.2	-	ns
Q_{rr}	Reverse Recovery Charge		-	4.1	-	nC
Dynamic Characteristics						
R_G	Gate Resistance	$V_{GS}=0V, V_{DS}=0V, F=1MHz$	-	1.5	2.7	Ω
C_{iss}	Input Capacitance	$V_{GS}=0V,$ $V_{DS}=10V,$ Frequency=1.0MHz	-	780	1015	pF
C_{oss}	Output Capacitance		-	170	-	
C_{rss}	Reverse Transfer Capacitance		-	120	-	
$t_{d(ON)}$	Turn-on Delay Time	$V_{DD}=10V, R_L=10\Omega,$ $I_{DS}=1A, V_{GEN}=4.5V,$ $R_G=1\Omega$	-	10.6	-	ns
t_r	Turn-on Rise Time		-	15	-	
$t_{d(OFF)}$	Turn-off Delay Time		-	17.2	-	
t_f	Turn-off Fall Time		-	4	-	
Gate Charge Characteristics						
Q_g	Total Gate Charge	$V_{ds}=10V, V_{gs}=4.5V,$ $I_{ds}=9A$	-	8.9	11.5	nC
Q_{gs}	Gate-Source Charge		-	0.52	-	
Q_{gd}	Gate-Drain Charge		-	3.8	-	

 Note d Pulse test ; pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$.


:

Typical Operating Characteristics


Power Dissipation




Drain Current



Safe Operation Area




Thermal Transient Impedance




Typical Operating Characteristics (Cont.)


Output Characteristics




Drain-Source On Resistance



Gate-Source On Resistance




Gate Threshold Voltage




Typical Operating Characteristics (Cont.)


Drain-Source On Resistance




Source-Drain Diode Forward





Capacitance





Gate Charge




Avalanche Test Circuit and Waveforms




Switching Time Test Circuit and Waveforms





SYMBOLS	MILLIMETERS		INCHES	
	MIN.	MAX.	MIN.	MAX.
	A	0.70	0.80	0.028
A1	0.00	0.05	0.000	0.002
A3	0.2 REF		0.008 REF	
b	0.25	0.35	0.010	0.014
D	1.90	2.10	0.075	0.083
D2	0.90	1.10	0.035	0.043
E	1.90	2.10	0.075	0.083
E2	0.80	1.00	0.031	0.039
e	0.55	0.75	0.022	0.030
H	0.25 REF		0.01 REF	
K	0.15		0.006	
K1	0.20		0.008	
K2	0.25		0.010	
L	0.20	0.30	0.008	0.012
L1	0.65	0.85	0.026	0.033

RECOMMENDED LAND PATTERN



UNIT: mm